

5位數微電腦型盤面式控制電錶(顯示幕0.8",48x96x85mm) (MICROPROCESS PANEL CONTROLLER METER)(DISPLAY 0.8",48x96x85mm)

MODEL
MM3S



■特點(FEATURES)

- 精確度0.05%滿刻度±1位數(Accuracy 0.05% F.S.±1 digit)
- 可量測 交直流電流/交直電壓/電位計/傳送器/Pt-100/熱電偶/荷重元/電阻 等信號
(Measuring DCA/DCV/ACA/ACV/Potentiometer/Transmitter/Pt-100/Thermocouple/Load Cell/Resistor/etc.....)
- 顯示範圍 -19999~99999可任意規劃(Programmable range -19999~99999 digit)
- 具有自動歸零與開根號與最大保持功能(Auto zero and math-rootextractor and maximum hold function)
- 具有16段線性折補功能(Correction for non-linearity function(16 segments)(optional))
- 4組警報功能(Max. four alarm function)(optional)
- 16BIT 類比輸出功能(16 bit DAC analog output function)(optional)
- 數位RS-485界面(Digit RS-485 interface function)(optional)

1.MODEL:MM3S-□ □ □ - □ □ □ X (X=NIL(None correction for non-linearity function),X=L(Correction for non-linearity function(16-segments)))

(選購型號)

NO	Input Type	NO	DCV(ACV)	NO	DCA(ACA)	NO	Transmitter	NO	Load Cell	NO	Thermocouple	NO	Alarm output	NO	Analog output	NO	RS-485	NO	Aux. Power
A	DC	11	0~50mV	21	0~99.999uA	41	DCA~20mA	61	2mV/V	71	J(-200~760)°C	0	None	0	None	N	None	A	AC/DC18~60V
B	AC(RMS)	12	0~5V	22	0~999.99mA	42	DC1~5V	62	3mV/V	72	K(-200~1360)°C	1	One	1	DC4~20mA	Y	RS-485	B	AC/DC90~260V
C	AC(TRMS)	13	0~10V	23	0~9999.9mA	43	DC4~20mA	63	2mV/V	73	T(-200~395)°C	2	Two	2	DC4~10V				Modbus mode •256 nodes on bus
D	Potentiometer	14	0~36V	24	0~99.99mA	44	DC1~5V	64	3mV/V	74	E(-185~990)°C	3	Three	3	•DC4~20mA				•Less 4VA for AC/DC input
E	Transmitter	15	0~54V	25	0~999.99mA	49	SPECIFIED	69	SPECIFIED	75	R(0~1760)°C	4	Four	9	SPECIFIED				
F	Pt-100(RTD)	16	0~110V	26	0~2.0000A					76	S(0~1750)°C								
G	Thermocouple	17	0~600V	27	0~5.0000A		•41/42 nonexciting DC24V •43/44 exciting DC24V(<25mA)			77	B(200~1800)°C								
H	Load Cell	18	0~10000V	28	0~10.000A		•61/62 Exciting DC5V(<50mA) •63/64 Exciting DC10V(<50mA)				•CJC traceability <=0.5°C(0~70°C)								
R	Resistor	19	SPECIFIED	29	SPECIFIED														

2.SPECIFICATION (主要規格)

- Measuring accuracy : 0.05% F.S.±1 digit
(精確度) (23±5°C) 0.2% F.S.±1 digit(AC(RMS)) 0.2% F.S.±0.5°C (CJC)(Thermocouple)
- Sampling time : 16 cycles/sec.
- Readout range : -19999~99999 digit adjustable
- Alarm delay time : 0~99.9 second adjustable
(繼電器延遲動作時間)
- Alarm action : HI or Lo adjustable
(繼電器動作方向)
- Relay contact output : AC 250V-5A, DC 30V-7A
(繼電器容量)
- Analog output resolution : 16 bit DAC
(類比輸出解析度)
- Response time : < 250ms(0~90%)
(輸出反應速度)
- Output drive capability : < 10mA for voltage mode
< 10V for current mode
<[(V+)-7.5V]/20mA for two-wire mode
(輸出負載能力)
- Output ripple (p-p) : < 0.1% F.S.
(輸出之漣波)
- RS-485 address : "01"~"FF"(0~255)
(通訊位址)
- RS-485 baud rate : 19200/9600/4800/2400 selective
(傳輸速度)
- RS-485 protocol : Modbus RTU mode
(通信協議)
- Temp. coefficient : 50ppm/°C (0~50°C)
(溫度係數)
- Display : Red high efficiency LEDs high 20.32mm(0.8")
(顯示幕)
- Parameter setting : Touch switches
(參數設定方式)
- Memory mode : Non-volatile E² PROM memory
(記憶型式)
- Dielectric strength : 2KVac/1 min. (input/output/power)
1600 Vdc (input/output)
(絕緣耐壓能力)
- Operating condition : 0~50°C (20 to 90% RH non-condensed)
(使用環境條件)
- Storage condition : 0~70°C (20 to 90% RH non-condensed)
(存放環境條件)
- CE EMC Certification : EN 55022:1998/A1:2000 Class A
EN 61000-3-2:2000
EN 61000-3-3:1995/A1:2001
EN 55024:1998/A1:2001
(CE認證)

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

